



Pre-Notice Announcement: New Model FT-6615Raid Product Information

Taipei, Taiwan, Dec. 26, 2008

Overview

Data security is a growing market requirement for businesses of all sizes today, and more and more business operation meets the problem with data storage and protection. In order to satisfy the data protection and provides non-stop operation, Posiflex develops the new FT-6615Raid Terminal, which is built in RAID-1 function with 2 internal 2.5" SATA HDD as well as supports Hot Swap, SteelVine Manager management software, error POP UP notification and SMTP e-mail notification.

This product is suitable for the market segments, which requires for higher level of data protection, for example Public Sector, for 24-hrsx365 days operation Retail, Hospitality etc.

Feature

- Support up to 2GB system memory.
- Built-in RAID Function with support of:
 - RAID 1(Disk Mirroring)
 - 2xSATA I or SATA II HDD
 - Hot swap
 - Management software via SteelVine Manager.
 - POP UP error notification
 - Windows XP pro, WEPOS, POSReady
 - SMTP e-mail notification
- Fan-free design and spill proof water resistant structure
- High quality 15" TFT active matrix LCD panel
- Brightness controlled by 2 push buttons in front of base unit.
- LED indicators for power status in front bezel and for HDD, LAN status in front of base unit
- COM port MODEM ring up and LAN wake up function



SPECIFICATION	FT-6615
CPU	Celeron M 1.5GHz W/ 1MB cache
VGA Interface	D-SUB 15 pins
VGA Memory	Share system memory up to 128MB
LCD Display	15" TFT LCD Panel, 1024 x 768 resolution
DRAM Memory	DDR2 SDRAM 533MHz, DIMM x 2, up to 2GB
Serial Port	4 x DB9, 1 x RJ45, each with +5V power supply, +12V reserved, (By software control=>6/24)
Parallel Port	1
CF Card Slot	Yes
CR Port	1
Standard USB Port	6 (2 for internal use, 1 in front, 3 in back)
KB Port	Yes
PS/2 Mouse Port	Yes
Audio Port	Line-out / Mic-in / W/ 2 W speaker in base unit
Ethernet Port	10/100/1000 MB
UPS Port	Yes
Touch Controller	USB interface
Touch Sensor	15" Resistance
Extension Slot	Yes
Storage Device	Internal SATA x 2
Power Supply	12 VDC power adaptor, 80 W
Fan-free System	Yes
OS Support	WEPOS, POSReady, WINXP Pro, Linux
Option Peripheral :	
PD-2603	VFD, 20x2 Pole Display
PD-308	LCD, 20x2 Pole Display
PD-7623	LCD, 4x15 or 4x30 Pole Display
FA-200	MSR + Optical fingerprint sensor
UPS Battery	2.3AH/12V Lead Acid battery
CD-ROM	Through USB port
RAID	Built in the HDD interface board
Wireless LAN	802.11 b/g with USB interface
CF Card Slot	Type II, for memory card only

** The product information and specifications are subject to change without prior notice.

Schedule

1. Engineer sample on 2008/12
2. Pilot run on 2009/01
3. Mass production on 2009/2

Remark: The above information is subject to change during the product development stage.
If any change will occur, will inform accordingly.

Posiflex Technologies, Inc.

6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan, R.O.C. Tel#: 886 2 2299-1599 Fax#: 886 2 2299-1819
www.posiflex.com.tw sales@posiflex.com.tw