



Product Launch Notice

**JIVA-8315E, HT-4612E, XP-3300E,
TX-3000E, TX-3100E, PB-4600E Series**

2011-04-01



**One-Stop Hardware
Solution Provider**

Dear Partners,

Posiflex launches the new models that enhance the existing ones by upgrading CPU and memory. Details are as the following:

Existing Model	Enhanced Model	CPU	Memory
JIVA-8315 Series	JIVA-8315E Series		Upgrade from DDR2 667 / 800 MHz, SO-DIMM Socket x 2, max 4 GB, default 1 GB To DDR3 1066 MHz, SO-DIMM Socket x 2, max 8 GB, default 2 GB
HT-4612 Series	HT-4612E Series		Upgrade from DDR2 667 / 800 MHz, DIMM Socket x 2, max 4 GB, default 1 GB To DDR3 1066 MHz, SO-DIMM Socket x 2, max 8 GB, default 1 GB
XP-3300 Series	XP-33100E Series	Upgrade from Intel Pine View D410 1.66 GHz Intel Pine View D510 Dual Core 1.66 GHz To Intel Pine View D425 1.8 GHz or Intel Pine View D525 Dual Core 1.8 GHz (Optional)	Upgrade from DDR2 667 MHz, SO-DIMM Socket x 1, max 2 GB, default 1 GB To DDR3 800 MHz, SO-DIMM Socket x 1, max 4 GB, default 1 GB
TX-3000 Series	TX-3000E Series	Upgrade from Intel Pine View D410 1.66 GHz To Intel Pine View D425 1.8 GHz	Upgrade from DDR2 667 MHz, SO-DIMM Socket x 1, max 2 GB, default 1GB To DDR3 800 MHz, SO-DIMM Socket x 1, max 4 GB, default 1 GB
	TX-3100E Series	Upgrade from Intel Pine View D510 Dual Core 1.66 GHz To Intel Pine View D525 Dual Core 1.8 GHz	
PB-4600 Series	PB-4600E Series		Upgrade from DDR2 667/800 MHz, DIMM Socket x 2, max 4 GB, default 1 GB To DDR3 1066 MHz, SO-DIMM Socket x 2, max 8 GB, default 1 GB

Ordering Models :

Model	Description
Jiva-8315E	Touch terminal, Intel Dual Core 2.1GHz, Resistive touch panel,15" TFT LCD, 2GB DDR3, 160GB HDD, No OS, option: 2nd HDD with RAID 1 module.
Jiva-8315E-I	Touch terminal, Intel Dual Core 2.1GHz,Infrared touch panel,15" TFT LCD, 2GB DDR3, 160GB HDD, No OS, option: 2nd HDD with RAID 1 module.
HT-4612E	Mini footprint 12.1" LCD (1024*768) terminal, Intel Dual Core 2.1GHz, 1GB DDR3 memory, 160GB HDD, No OS. Option: 2nd HDD with RAID 1 module.
HT-4612H-E	Mini footprint 12.1" LCD (1024*768) touch terminal, Intel Dual Core 2.1GGHz, 1GB DDR3 memory, 160GB HDD, No OS. option: 2nd HDD with RAID 1 module.
XP-3312H-E	All-in-one touch terminal Pine View-1.8G with 12.1" LCD(1024*768) and 3" high speed (150mm/sec) thermal printer with auto cutter. 1GB DDR3, 160GB HDD. No OS, Option:UPS, MSR, 2nd display
XP-3315H-E	All-in-one touch terminal Pine View-1.8G with 15" LCD (1024*768) and 3" high speed (150mm/sec) thermal printer with auto cutter. 1GB DDR3, 160GB HDD. No OS, Option:UPS, MSR, 2nd display
TX-3000E	POS box Intel Pine View SC 1.8G, 1GB DDR3, 160GB HDD, 4S, 4USB, PS/2 cable, no OS.
TX-3000S-E	POS box Intel Pine View SC 1.8G, 1GB DDR3, 160GB HDD, 4S, 4USB, PS/2 cable, no cable cover, no OS.
TX-3100E	POS box Intel Pine View Dual core 1.8G, 1GB DDR3, 160GB HDD, 4S, 4USB, PS/2 cable, no OS.
TX-3100S-E	POS box Intel Pine View Dual core 1.8G, 1GB DDR3, 160GB HDD,4S, 4USB,PS/2 cable, no cable cover, no OS.
PB-4600E	POS box Intel Dual Core 2.1G, 1GB DDR3, 160GB HDD, 4S1P, 6USB, no OS. Option: 2nd HDD with RAID 1 module.

Please send in your demands or contact your sales representative for the further arrangement. If you have any questions pertaining to this announcement, please do not hesitate to contact your sales representative.

Note : For detailed specification, please refer to our brochure, website or quotation.

Posiflex Technology, Inc.

6, Wu-Chuan Road, Wu Ku, Taipei, Taiwan, R.O.C. Tel#: 886 2 2299-1599 Fax#: 886 2 2299-1819
www.posiflex.com sales@posiflex.com.tw