

ZT-3115/3115E/3116/3116E

Specification	ZT-3115	ZT-3115E	ZT-3116	ZT-3116E
Processor	Intel Elkhart Lake Celeron J6412, up to 2.60 GHz, 1.5M Cache			
System Memory	DDR4 SO-DIMM x 2, max. 32GB			
Storage Device	M.2 connector [SATA Signal Only] x 2			
RAID Function	N/A			
Intel vPro Support	N/A			
TPM Support	TPM 2.0			
Power Supply	24V/60W	24V/120W	24V/60W	24V/120W
OS Support	Windows 10 IoT/ Windows 11			
Display & Touch				
LCD	15" TFT LCD		15.6" TFT LCD	
Resolution	1024 x 768		1920 x 1080	
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)			
I/O & Expansion				
Serial Port	2, DB9 x 1 + RJ50 x 1 (5V/12V support on all COM ports)			
Standard USB Port	5, USB 3.0 x 2 + USB 2.0 x 3			
PoweredUSB Port	N/A	24V PoweredUSB x 1	N/A	24V PoweredUSB x 1
OTG USB	N/A			
LAN Port	10/100/1000 Mb x 2			
Display Port	1. Proprietary connector x 1 for 2nd display, 2. USB Type-C x 1			
CR Port	1, control 2 CR via optional Y-cable, supporting 24V cash drawer			
Audio	Internal 2W speaker x 1			
Expansion Slot	M.2 2230 x 1 for Wi-Fi/BT			
Physical Dimension				
Dimension (W x D x H in mm)	353 x 206 x 319		376 x 206 x 304	
Weight (N. W. in kg)	4.9		4.5	
Environmental				
Operating Condition	0°C - 40°C, 20%RH - 90%RH			
Storage Condition	-20°C - 70°C, 10%RH - 90%RH			
Built-in Options				
WiFi	M.2 WiFi/BT module			
Camera	1MP wide angle camera			
AG Glass	Cannot coexist with built-in camera			
Attachment Options				
POS Monitor	PCAP touch TFT LCD: 10.1"			
Line Display	N/A			
Attachment	MSR; 2D Scanner; RFID; Fingerprint Sensor			



Driving Innovation and Business Efficiency

ZT-3115/3115E/3116/3116E

Fanless POS Terminal